

CHRONO is our new mobile sanding station provided with a 2-motor vacuum cleaner, with or without filter shaker and with automatic start. It can be used with 2 different tools at the same time.



CHRONO

BL250SS BL250SSV

Motors	2	2
Stage	double	double
Volt (V)	220-240	220-240
Frequency (Hz)	50/60	50/60
Cooling	by pass	by pass
P max motor (W)	2600	2600
P max tool (W)	1200	1200
Pressure min-max (bar)	4-15	4-15
Waterlift (mm H ₂ O)	2400	2400
Air flow (m ³ /h)	430	430
LpA sonorus 3mt(dB(A))	67	67
Total tank capacity (lt)	77	77
Filter shaker	NO	YES



for electric and pneumatic tools



- 1 Flexible hose 5,0mt ø28 complete
- 2 Flexible with pneumatic hose ø 28 - 5,0mt
- 3 Y Coupling inlet

ACTF028/5/CY (standard)
ACTF028P5CY (standard)
ACMD040N/C (standard)



- 4 Crevice tool ø40
- 5 Chrome curved extension wand-male ø40
- 6 Chrome extension wand ø40
- 7 Dusting brush ø40
- 8 Nozzle body A/P L400 ø40
- 9 Slide-on brush for floor nozzle L400
- 10 Complete flexible hose mt. 2,5 ø40
- 11 Spring rod

ACLP040 (optional)
ACTC038C (optional)
ACTC038D (optional)
ACPE040 (optional)
ACCS400A/P (optional)
ACIP400 (optional)
ACTF038/2,5/C (optional)
CMAS008 (optional)

Accessories



- 12 Polyester filter with ring ø440
- 13 Polyester bag 77 lt Max 2 mot
- 14 Cartridge filter ø250 - H178
- 15 Nylon filter ø440
- 16 Sponge filter for liquids

FA044P (standard for BL250SS)
FI005PT (standard for BL250SS and BL250SSV)
FI250178P (standard for BL250SSV)
FINY440AT (standard for BL250SS)
ACCA165A (standard for BL250SS)

Filters